

THE COMPACT A3 PRINTER FOR WORKGROUPS.

The FS-6970DN is the ideal solution for workgroups that require a wide variety of output sizes up to A3. The fast and compact printer offers an expandable paper capacity of up to 6 paper trays for flexible paper handling. Furthermore, this team player knows how to impress with comprehensive security features and ECOSYS Longlife Technology for exceptionally low cost per page.

- ▶ Up to 35 pages per minute in A4, up to 17 per minute in A3
- ▶ Standard duplex unit for double-sided printing
- ▶ Up to 6 paper trays for superior flexibility and up to 1,350 sheets
- ▶ PowerPC 440 / 600 MHz, 128–1,152 MB RAM, optional hard disk
- ▶ USB, parallel and network connectivity as standard
- ▶ High security with SSL encryption
- ▶ Direct PDF Print from USB Flash memory device
- ▶ Exceptionally low printing costs in its class



The FS-6970DN is able to cope with large print volumes and additionally offers a high amount of flexibility, thanks to up to 6 paper trays for a total of 1,350 sheets.

Now also as standard for A3: enhanced security features such as network authentication, IPV6, IP sec and SSL encryption.



FS-6970DN

MONOCHROME WORKGROUP PRINTER FOR A3 FORMATS



ECOSYS stands for ECOlogy,
ECOonomy and SYStem-printing.

With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

PRESCRIBE IIe

With the KYOCERA page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

The KM NetViewer

The KM NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Status Monitor and Command Center

The Status Monitor shows the current printers condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

General

Technology

KYOCERA ECOSYS Laser

Engine speed

Up to 35/17 pages per minute in A4/A3

Resolution

1,200 dpi

Duty cycle

Max. 150,000 pages per month

Max. average 20,000 pages per month

Warm-up time

Approx. 15 seconds or less from power on

Time to first page

Approx. 9 seconds or less

Dimensions (W x D x H)

Main unit: 469 mm x 395 mm x 285 mm

Weight

Main unit: approx. 19.5 kg

Power source

AC 220-240 V, 50/60 Hz

Power consumption

Printing: 516 W

Stand-by: 9.6 W

Power-Saving (ECOpower): 6.3 W

Noise (ISO 7779 / ISO 9296)

Printing: 51 dB(A)

Stand-by: 29 dB(A)

Power-Saving (ECOpower): Immeasurably low

Safety standards

GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

100-sheet multi-purpose tray; 60-220 g/m²;

A3, B4, A4-R, A4, A5, A6-R, B5, Letter, Letter-R, Legal,

Ledger, Custom (70 x 148 mm to 297 x 450 mm)

250-sheet universal paper cassette, 60-120 g/m²;

A3, B4, A4-R, A4, A5, B5, Letter, Letter-R, Legal, Ledger,

Custom (140 x 148 mm to 297 x 432 mm)

Max. input capacity incl. options: 1,350 sheets

Duplex unit

Duplex as standard supports A3-A5-R, 60-120 g/m²

Output capacity

250 sheets face-down with paper full sensor and optional

250 sheets face-up with PT-430

Controller

CPU

PowerPC 440/600 MHz

Memory

Standard 128 MB, max. 1,152 MB

Standard interface

High-speed bi-directional parallel (IEEE 1284), USB 2.0

(Hi-Speed), USB Host Interface dedicated for USB Flash

Memory device, Fast Ethernet 10Base-T/100Base-TX,

Slot for optional internal print server or hard disc

Slot for optional CompactFlash®-Card

Controller language

PRESCRIBE IIe

Emulations

PCL6/PCL5c incl. PJI, KPDL 3 (PostScript 3 compatible),

KC-GL (HP-7550A), PDF Direct Print, Line Printer, IBM

Proprinter X24E, Epson LQ-850, Diablo 630

Operating systems

All current Windows operating systems,

Mac OS X Version 10.2 or higher,

UNIX, LINUX as well as other operating systems on request

Fonts/barcodes

93 scalable fonts for PCL/PostScript®, 8 fonts for Windows

Vista®, 1 Bitmap font, 45 barcodes (e.g. EAN8, EAN13,

EAN128) with automatic generation of checksums as well

as support of two-dimensional barcodes PDF-417 under

PRESCRIBE (PCL and other barcodes available as an option)

Integrated accounting

100 department codes

Consumables

TK-450 Toner-kit

Microfine toner for 15,000 pages in accordance with ISO/

IEC 19752

Capacity of starter toner is 7,500 pages in accordance

with ISO/IEC 19752

Options

Paper handling

PF-430 Paper feeder (max. 4 units)

Max. 250 sheets; 60-120 g/m²; A3, B4, A4-R, A4, A5, B5, Letter, Letter-R, Legal, Ledger, Custom (140 x 210 mm to 297 x 432 mm)

PT-430 Bulk Paper tray

250 sheets face-up output tray

Memory upgrade

MDDR2-128: 128 MB; MDDR2-256: 256 MB;

MDDR2-512: 512 MB, MDDR2-1024: 1.024 MB

CompactFlash®-Card

1 slot (up to 4 GB) for printing forms, fonts, logos, macro storage

USB Flash Memory

Supports PDF direct printing via USB Host Interface

HD-5a Hard disc

40 GB for easy document management

Optional interface

PS159: Wireless LAN (802.11b/g)

PS1109 Gigabit Ethernet:

10BaseT / 100BaseTX / 1000BaseT (RJ-45)

PS129 Fibre Optic: 100BaseSX (SC)

PS1129 Gigabit Fibre Optic: 1000BaseSX (SC)

Model variations

FS-6970DN/KL3

FS-6970DN incl. warranty extension KYOLife 3 years

Warranty

2-year warranty as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 300,000 pages A4 (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

KYO LIFE The up to 5-year on-site warranty extension for printer and options.



Your KYOCERA Business Partner:

KYOCERA MITA Europe B.V. – Branch Office Germany – Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany

Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100

www.kyoceramita-europe.com – info@kyoceramita-europe.com

KYOCERA MITA Corporation – 2-28, 1-Chome – Tamatsukuri – Chuo-Ku

Osaka 540-8585 – Japan – www.kyoceramita.com

* KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



Product depicted includes optional extras.

KYOCERA