

WDR

HI-SPEED

SMART

RELIABLE

IQeye510

WIDE DYNAMIC RANGE IP CAMERA



Wide VGA and Global Shutter

Ideal for high speed applications like traffic, transportation and casinos, the IQeye510 Network Camera's global shutter technology captures high resolution images without the distortion that occurs with interlaced technology. The Wide VGA format lets you cover a wider area, so deployment is cost-effective, and Wide Dynamic Range lets you capture all the details in the most challenging lighting environments.


The IQeye510 delivers real-time, high quality video and best-in-class low-light performance in an attractive, low-profile industrial package. Installation and maintenance is simple and inexpensive with features like Power Over Ethernet and IQfocus™ utility. Like every IQeye, the IQeye510 is built on IQinVision's world class operating system that offers unmatched network stability and reliability, so you *never miss a thing*.

www.iqeye.com

*For a complete list of compatible NVR/DVR systems, please visit www.iqeye.com.

IQinVision 
When you can't afford to miss a thing.

IQeye510 - Global Shutter



CCTV Quality

IQrecorder™

Available with every IQeye, IQrecorder enables you to record and playback crisp, clear IQeye Resolution™ images using affordable network storage *with no client software*.

IQauthenticate™

Every IQeye is also available with on-camera, digital authentication that protects images right in the camera. IQauthenticate addresses the image manipulation problem *at the source* ensuring your evidence has not been compromised.




IQfocus™

The IQfocus utility lets you use popular hand-held CCTV monitors and eliminates the hassles of focusing cameras over slow networks.



IQeye Quality

- **Global Shutter**
- **Wide Dynamic Range, up to 100dB**
- **Wide VGA Resolution (752 x 480)**
- **Up to 60+ ips @ 752 x 480**
- **IEEE 802.3af - Power-Over-Ethernet**
- **0.4 lux low-light performance**
- **LIGHTGRABBER™ low light technology**
- **Digital PTZ with no moving parts**
- **Multi-zone motion detection**
- **Digital image cropping**
- **Privacy zones**
- **Advanced bandwidth management tools**
- **Proven network reliability**
- **User-selectable exposure window**
- **AC/DC or IEEE 802.3af**
- **< 2.5 watts, AC or DC**

CAMERA MODEL	LENS OPTIONS	POWER SUPPLY	ENCLOSURE TYPE
 IQ510 Camera - Wide Dynamic Range, WVGA Camera, 60ips, 0.4 lux	NL - No Lens V3 - Wide Varifocal Lens V4 - Telephoto Varifocal Lens W1 - Ultra Wide Varifocal Lens	NP - No Power Supply	NE - No Enclosure
 IQ510 Vandal Dome 4"- Wide Dynamic Range, WVGA Camera, 60ips, 0.4 lux	B1 - Wide Varifocal Lens	NP - No Power Supply	DV - Interior/Exterior Vandal Dome
 IQ510 Outdoor Housing 9.5"- Wide Dynamic Range, WVGA Camera, 60ips, 0.4 lux	NL - No Lens V3 - Wide Varifocal Lens V4 - Telephoto Varifocal Lens	NP - No Power Supply	X2 - Outdoor Housing, IP 65/NEMA 4
Part Number Example - IQ510NLNPNE - Wide Dynamic Range, WVGA Camera, 60ips, 0.4 lux, No Lens, No Power Supply, No Enclosure			

Camera dimensions (without lens) approx. 2.9"(7.4cm)H x 3.5"(8.9cm)W x 1.7"(4.3cm)D
 Camera weight (without lens) 6oz (160g)
 For shipping weight information, please contact IQinVision.

©2008 IQinVision, Inc., IQinVision, IQeye logo are registered trademarks, and IQeye, IQfocus, IQauthenticate, IQrecorder, IQeye Resolution and LIGHTGRABBER are trademarks of IQinVision. All other brands, trademarks and/or registered trademarks are property of their respective holders. 1208

When you can't afford to miss a thing.

IQinVision 
www.iqeye.com

33122 Valle Road
 San Juan Capistrano, CA 92675-4853 USA
 toll-free within U.S. 877.850.0805
 phone +1.949.369.8100
 fax +1.949.369.8105